

AXTON
ILLUMINATE THE NIGHT

PRICE LIST 2018

CONTENTS



| | |
|--|---------|
| <u>SMART SERIES</u> Essential IR | 3 |
| <u>MEGAPIXEL SERIES</u> PoE IR | 4 |
| <u>ZOOM SERIES</u> Multi-Angle IR | 5 |
| <u>ORION SERIES</u> Basic IR | 6 |
| <u>NANO SERIES</u> Compact IR | 7 |
| <u>OMNI SERIES</u> Indoor Fixture IR | 8 |
| <u>HYBRID SERIES</u> IR and Visible Light | 9 |
| <u>BLAZE SERIES</u> White Light | 10 |
| <u>XLR SERIES</u> Extra Long Range IR | 11 |
| <u>PANORAMIC SERIES</u> Extra Wide Angle IR | 12 - 14 |
| <u>HYBRID PANORAMIC SERIES</u> Wide Angle IR and Visible Light | 15 - 17 |
| <u>POWER SUPPLIES</u> | 18 |
| <u>BRACKETS</u> & Mounting Adapters | 19 |



Lifetime Warranty
with advanced replacement



Fast Delivery
Most orders ship within 48 hours.





Made in the USA
Designed and manufactured in the USA

SMART Series Infrared

ESSENTIAL INFRARED



SMART AT-11S | SMART AT-25S | SMART AT-56S

| MODEL | DESCRIPTION | ANGLE OPTIONS | RANGE | | PART NUMBER | PRICE |
|---|-------------|---------------|----------|------------------|-------------|-------|
| | | | Distance | HFOV | | |
|  <p>AT-11S</p> <ul style="list-style-type: none"> • 11 Watts • Day/Night Sensor • I/O Ports • 24-36VDC or 24VAC Input[†] • 850nm IR • Pan/Tilt U Bracket • IP67 Rated | 10° | 540ft | 94ft | AT-11S.11S2810 | \$FPO | |
| | 20° x 10° | 360ft | 112ft | AT-11S.11S282010 | | |
| | 30° | 270ft | 140ft | AT-11S.11S2830 | | |
| | 60° x 30° | 190ft | 190ft | AT-11S.11S286030 | | |
| | 90° | 120ft | 152ft | AT-11S.11S2890 | | |
| | 150° | 80ft | 155ft | AT-11S.11S28150 | | |
|  <p>AT-25S</p> <ul style="list-style-type: none"> • 25 Watts • Day/Night Sensor • I/O Ports • 24-36VDC or 24VAC Input[†] • 850nm IR • Pan/Tilt U Bracket • IP67 Rated | 10° | 800ft | 140ft | AT-25S.25S2810 | \$FPO | |
| | 20° x 10° | 530ft | 166ft | AT-25S.25S282010 | | |
| | 30° | 400ft | 207ft | AT-25S.25S2830 | | |
| | 60° x 30° | 285ft | 285ft | AT-25S.25S286030 | | |
| | 90° | 175ft | 225ft | AT-25S.25S2890 | | |
| | 150° | 120ft | 232ft | AT-25S.25S28150 | | |
|  <p>AT-56S</p> <ul style="list-style-type: none"> • 56 Watts • Day/Night Sensor • I/O Ports • 24-36VDC or 24VAC Input[†] • 850nm IR • Pan/Tilt U Bracket • IP67 Rated | 10° | 1200ft | 209ft | AT-56S.56S2810 | \$FPO | |
| | 20° x 10° | 800ft | 250ft | AT-56S.56S282010 | | |
| | 30° | 600ft | 310ft | AT-56S.56S2830 | | |
| | 60° x 30° | 420ft | 420ft | AT-56S.56S286030 | | |
| | 90° | 270ft | 347ft | AT-56S.56S2890 | | |
| | 150° | 185ft | 357ft | AT-56S.56S28150 | | |

NOTE: Simplified "A"(no I/O port) or "B" (no Day/Night Sensor or I/O Ports) models are also available.

For quantities over 10 please contact us for pricing.

[†]Power supply options available; please see our power supply page.

PRIMARY FEATURES ~ Low Voltage - 850nm Infrared - Day/Night Sensor - I/O Ports - Outdoor IP67 Rated - Pan/Tilt U bracket Included
 Please see our website (link below) for additional product details.

SMART



801 West Robinson Drive, Suite 500, North Salt Lake, UT 84054

☎ 801/519-0500 📠 801/519-0501 ✉ sales@axtontech.com 📧 orders@axtontech.com






MEGAPIXEL Series Infrared

PoE POWERED INFRARED



[MEGAPIXEL AT-11E-S](#) | [MEGAPIXEL AT-25E-S](#) | [MEGAPIXEL AT-56E-S](#)

| MODEL | DESCRIPTION | ANGLE OPTIONS | RANGE | | PART NUMBER | PRICE |
|--|-------------|---------------|----------|---------------------|--------------|-------|
| | | | Distance | HFOV | | |
|  AT-11E-S <ul style="list-style-type: none"> • 11 Watts • Day/Night Sensor • I/O Ports • PoE or PoE + Input • 850nm IR • Pan/Tilt U Bracket • IP67 Rated | 10° | 540ft | 94ft | AT-11E-S.11ES3810 | \$FPO | |
| | 20° x 10° | 360ft | 112ft | AT-11E-S.11ES382010 | | |
| | 30° | 270ft | 140ft | AT-11E-S.11ES3830 | | |
| | 60° x 30° | 190ft | 190ft | AT-11E-S.11ES386030 | | |
| | 90° | 120ft | 152ft | AT-11E-S.11ES3890 | | |
| | 150° | 80ft | 155ft | AT-11E-S.11ES38150 | | |
|  AT-25E-S <ul style="list-style-type: none"> • 24 Watts • Day/Night Sensor • I/O Ports • PoE+ or PoE++ Input • 850nm IR • Pan/Tilt U Bracket • IP67 Rated | 10° | 800ft | 140ft | AT-25E-S.25ES3810 | \$FPO | |
| | 20° x 10° | 530ft | 166ft | AT-25E-S.25ES382010 | | |
| | 30° | 400ft | 207ft | AT-25E-S.25ES3830 | | |
| | 60° x 30° | 285ft | 285ft | AT-25E-S.25ES386030 | | |
| | 90° | 175ft | 225ft | AT-25E-S.25ES3890 | | |
| | 150° | 120ft | 232ft | AT-25E-S.25ES38150 | | |
|  AT-56E-S <ul style="list-style-type: none"> • 56 Watts • Day/Night Sensor • I/O Ports • PoE++ Input • 850nm IR • Pan/Tilt U Bracket • IP67 Rated | 10° | 1200ft | 209ft | AT-56E-S.56ES3810 | \$FPO | |
| | 20° x 10° | 800ft | 250ft | AT-56E-S.56ES382010 | | |
| | 30° | 600ft | 310ft | AT-56E-S.56ES3830 | | |
| | 60° x 30° | 420ft | 420ft | AT-56E-S.56ES386030 | | |
| | 90° | 270ft | 347ft | AT-56E-S.56ES3890 | | |
| | 150° | 185ft | 357ft | AT-56E-S.56ES38150 | | |

NOTE: Simplified "A" (no I/O port) or "B" (no Day/Night Sensor or I/O Ports) models are also available.

For quantities over 10 please contact us for pricing.

PRIMARY FEATURES ~ PoE Powered - 850nm Infrared - Day/Night Sensor - I/O Ports - Outdoor IP67 Rated - Pan/Tilt U bracket Included

Please see our website (link below) for additional product details.

MEGAPIXEL



801 West Robinson Drive, Suite 500, North Salt Lake, UT 84054



☎ 801/519-0500 📠 801/519-0501 ✉ sales@axtontech.com ✉ orders@axtontech.com



ZOOM Series Infrared

MULTIPLE ANGLES IN ONE UNIT

ZOOM AT-15Z | PANORAMIC ZOOM AT-45Z

| MODEL | DESCRIPTION | ANGLES (in one unit) | RANGE | | PART NUMBER | PRICE |
|---|---|-------------------------|----------|-------|--|-------|
| | | | Distance | HFOV | | |
| AT-15Z-S  | <ul style="list-style-type: none"> • 15 Watts • Day/Night Sensor • I/O Ports • 24-36VDC or 24VAC Input† • 850nm IR • Pan/Tilt U Bracket • IP67 Rated | 90° | 145ft | 205ft | AT-15Z-S.15ZS28 | \$FPO |
| | | 60° x 30° | 230ft | 230ft | | |
| | | 20° x 10° | 430ft | 150ft | | |
| AT-45Z-S**  | <ul style="list-style-type: none"> • 45 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 90° | 250ft | 350ft | AT-45Z-S.45ZS28 <i>(LOW VOLTAGE 24-36VDC or 24VAC Input)</i> | \$FPO |
| | | 270° | 145ft | 290ft | | |
| | | 60° x 30° | 400ft | 400ft | AT-45Z-S.45ZS48 <i>(HIGH VOLTAGE Includes Power Supply, 110V AC to 240 VAC Input)</i> | \$FPO |
| | | 180° x 30° | 230ft | 460ft | | |
| | | 20° x 10° | 740ft | 255ft | | |
| | | 60° x 10° | 430ft | 460ft | | |

*Requires AT-8062-(C, P or W) Mounting Bracket for Installation.

For quantities over 10 please contact us for pricing.

** Each zoom unit has 3 built in angle options, the additional ranges for Panoramic ZOOM AT-45Z requires physical adjustment of the panels on mounting system. See website link below for details.

†Power supply options available; please see our power supply page.

PRIMARY FEATURES ~ Multiple angle options in one unit - 850nm Infrared - Day/Night Sensor - I/O Ports - Outdoor IP67 Rated Pan/Tilt Mounting Included

Please see our website (link below) for additional product details.

ZOOM

ORION Series Infrared

SIMPLE INFRARED LOW VOLTAGE & PoE

ORION-S (E) | ORION-M (E) | ORION-L (E)

| MODEL | DESCRIPTION | ANGLE OPTIONS | RANGE | | PART NUMBER | PRICE |
|--------------------|---|---------------|----------|-------|-----------------|--------------|
| | | | Distance | HFOV | | |
| ORION-S | <ul style="list-style-type: none"> • 8 Watts • Day/Night Sensor • 24-36VDC or 24VAC Input† • 850nm IR • IP67 Rated | 120° | 60ft | 108ft | AT-8N.8N28120 | \$FPO |
| | | 60° | 110ft | 100ft | AT-8N.8N2860 | |
| | | 30° | 165ft | 86ft | AT-8N.8N2830 | |
| ORION-M | <ul style="list-style-type: none"> • 16 Watts • Day/Night Sensor • 24-36VDC or 24VAC Input† • 850nm IR • IP67 Rated | 120° | 85ft | 158ft | AT-16N.16N28120 | \$FPO |
| | | 60° | 155ft | 141ft | AT-16N.16N2860 | |
| | | 30° | 230ft | 119ft | AT-16N.16N2830 | |
| ORION-L | <ul style="list-style-type: none"> • 32 Watts • Day/Night Sensor • 24-36VDC or 24VAC Input† • 850nm IR • IP67 Rated | 120° | 129ft | 215ft | AT-32N.32N28120 | \$FPO |
| | | 60° | 210ft | 190ft | AT-32N.32N2860 | |
| | | 30° | 320ft | 165ft | AT-32N.32N2830 | |

PoE Powered Options:

| MODEL | DESCRIPTION | ANGLE OPTIONS | RANGE | | PART NUMBER | PRICE |
|----------------------|--|---------------|----------|-------|-------------------|--------------|
| | | | Distance | HFOV | | |
| ORION-S-E | <ul style="list-style-type: none"> • 6 Watts • Day/Night Sensor • PoE Input • 850nm IR • IP67 Rated | 120° | 50ft | 90ft | AT-6NE.6NE38120 | \$FPO |
| | | 60° | 82ft | 75ft | AT-6NE.6NE3860 | |
| | | 30° | 130ft | 68ft | AT-6NE.6NE3830 | |
| ORION-M-E | <ul style="list-style-type: none"> • 12 Watts • Day/Night Sensor • PoE Input • 850nm IR • IP67 Rated | 120° | 70ft | 126ft | AT-12NE.12NE38120 | \$FPO |
| | | 60° | 115ft | 105ft | AT-12NE.12NE3860 | |
| | | 30° | 180ft | 95ft | AT-12NE.12NE3830 | |
| ORION-L-E | <ul style="list-style-type: none"> • 24 Watts • Day/Night Sensor • PoE Input • 850nm IR • IP67 Rated | 120° | 100ft | 176ft | AT-24NE.24NE38120 | \$FPO |
| | | 60° | 165ft | 146ft | AT-24NE.24NE3860 | |
| | | 30° | 260ft | 133ft | AT-24NE.24NE3830 | |

NOTE: Simplified "B" (no Day/Night Sensor) models are also available.

For quantities over 10 please contact us for pricing.





†Power supply options available; please see our power supply page.

PRIMARY FEATURES ~ Low Voltage or PoE Options - 850nm Infrared - Day/Night Sensor - Outdoor IP67 Rated - U bracket Included

NANO Series Infrared

COMPACT INFRARED - POE OR LOW VOLTAGE

[NANO AT-3M-S](#) | [NANO AT-5MS](#) | [NANO AT-5ME-A](#) | [NANO AT-3S-B](#)

| MODEL | DESCRIPTION | ANGLE OPTIONS | RANGE | | PART NUMBER | PRICE |
|---|-------------|---------------|----------|---------------------|-------------|-------|
| | | | Distance | HFOV | | |
|  AT-3M-S <ul style="list-style-type: none"> • 3 Watts • Day/Night Sensor • I/O Ports • (9 - 18)V DC Input† • 850nm IR • Mounting Bracket Included • IP67 Rated | 10° | 280ft | 50ft | AT-3M-S.3MS1810 | \$FPO | |
| | 20° x 10° | 190ft | 60ft | AT-3M-S.3MS182010 | | |
| | 30° | 140ft | 72ft | AT-3M-S.3MS1830 | | |
| | 60° x 30° | 100ft | 100ft | AT-3M-S.3MS186030 | | |
| | 90° | 62ft | 80ft | AT-3M-S.3MS1890 | | |
| | 130° | 44ft | 80ft | AT-3M-S.3MS18130 | | |
|  AT-5M-S <ul style="list-style-type: none"> • 5 Watts • Day/Night Sensor • I/O Ports • (9 - 18)V DC Input† • 850nm IR • Mounting Bracket Included • IP67 Rated | 10° | 370ft | 65ft | AT-5M-S.5MS1810 | \$FPO | |
| | 20° x 10° | 250ft | 78ft | AT-5M-S.5MS182010 | | |
| | 30° | 185ft | 96ft | AT-5M-S.5MS1830 | | |
| | 60° x 30° | 130ft | 130ft | AT-5M-S.5MS186030 | | |
| | 90° | 82ft | 105ft | AT-5M-S.5MS1890 | | |
| | 130° | 58ft | 105ft | AT-5M-S.5MS18130 | | |
|  AT-5ME-A <ul style="list-style-type: none"> • 5 Watts • Day/Night Sensor • PoE Input • 850nm IR • Mounting Bracket Included • IP67 Rated | 10° | 370ft | 65ft | AT-5ME-A.5MEA3810 | \$FPO | |
| | 20° x 10° | 250ft | 78ft | AT-5ME-A.5MEA382010 | | |
| | 30° | 185ft | 96ft | AT-5ME-A.5MEA3830 | | |
| | 60° x 30° | 130ft | 130ft | AT-5ME-A.5MEA386030 | | |
| | 90° | 82ft | 105ft | AT-5ME-A.5MEA3890 | | |
| | 130° | 58ft | 105ft | AT-5ME-A.5MEA38130 | | |
|  AT-3S-B (CUBE) <ul style="list-style-type: none"> • 3 Watts • (9 - 18)V DC Input† • 850nm IR • Mounting Bracket Included • Indoor Use Only | 10° | 141ft | 28ft | AT-3S-B.3SB1810 | \$FPO | |
| | 30° | 97ft | 50ft | AT-3S-B.3SB1830 | | |
| | 60° | 65ft | 58ft | AT-3S-B.3SB1860 | | |
| | 130° | 35ft | 63ft | AT-3S-B.3SB18130 | | |

NOTE: Simplified "A" (no I/O port) or "B" (no Day/Night Sensor or I/O Ports) models are also available.

For quantities over 10 please contact us for pricing.

†Power supply options available; please see our power supply page.



PRIMARY FEATURES ~ Compact: Max. Length 3.5" - Low Voltage and PoE options - 850nm Infrared - Outdoor IP67 Rated (excluding cube) - I/O Port Options: 3M-S & 5M-S

Please see our website (link below) for additional product details.

OMNI Series Infrared

COMPACT INDOOR FIXTURE INFRARED

OMNI AT-3LE | OMNI AT-5LE

| MODEL | DESCRIPTION | ANGLE | RANGE | | PART NUMBER | PRICE |
|---|---|-------|------------------------|----------|------------------|-------|
| | | | Distance | Coverage | | |
| AT-3LE  | <ul style="list-style-type: none"> • 3 Watts • 12VDC or PoE input[†] • 850nm IR • Indoor Use Only | 150° | 45.5ft/ 2,070 sq ft | 150° | AT-3LE.3LE138150 | \$FPO |
| AT-5LE  | <ul style="list-style-type: none"> • 5 Watts • 12VDC or PoE input[†] • 850nm IR • Indoor Use Only | 150° | 54ft/ 4,600 sq ft | 150° | AT-5LE.5LE138150 | \$FPO |

[†]Power supply option available; please see our power supply page.

For quantities over 10 please contact us for pricing.

PRIMARY FEATURES ~ Low Voltage or PoE - 850nm Infrared - Indoor Recessed Mounting - Rugged , Vandal Resistant

Please see our website (link below) for additional product details.






OMNI

HYBRID Series IR & White

INFRARED & EVENT ACTIVATED WHITE LIGHT



HYBRID AT-11H-S | HYBRID AT-25H-S | HYBRID AT-56H-S

| MODEL | DESCRIPTION | ANGLE OPTIONS | RANGE | | PART NUMBER | PRICE |
|--|-------------|---------------|----------|----------------------|-------------|-------|
| | | | Distance | HFOV | | |
| AT-11H-S  <ul style="list-style-type: none"> • 11 Watts • I/O Ports • 24-36VDC or 24VAC Input[†] • Visible/ 850nm IR • Pan/Tilt U Bracket • IP67 Rated | 10° | 540ft | 94ft | AT-11H-S.11HS21810 | \$FPO | |
| | 20° x 10° | 360ft | 112ft | AT-11H-S.11HS2182010 | | |
| | 30° | 270ft | 140ft | AT-11H-S.11HS21830 | | |
| | 60° x 30° | 190ft | 190ft | AT-11H-S.11HS2186030 | | |
| | 90° | 120ft | 152ft | AT-11H-S.11HS21890 | | |
| | 150° | 80ft | 155ft | AT-11H-S.11HS218150 | | |
| AT-25H-S  <ul style="list-style-type: none"> • 20 Watts • I/O Ports • 24-36VDC or 24VAC Input[†] • Visible/ 850nm IR • Pan/Tilt U Bracket • IP67 Rated | 10° | 800ft | 140ft | AT-25H-S.25HS21810 | \$FPO | |
| | 20° x 10° | 530ft | 166ft | AT-25H-S.25HS2182010 | | |
| | 30° | 400ft | 207ft | AT-25H-S.25HS21830 | | |
| | 60° x 30° | 285ft | 285ft | AT-25H-S.25HS2186030 | | |
| | 90° | 175ft | 225ft | AT-25H-S.25HS21890 | | |
| | 150° | 120ft | 232ft | AT-25H-S.25HS218150 | | |
| AT-56H-S  <ul style="list-style-type: none"> • 56 Watts • I/O Ports • 24-36VDC or 24VAC Input[†] • Visible/ 850nm IR • Pan/Tilt U Bracket • IP67 Rated | 10° | 1200ft | 209ft | AT-56H-S.56HS21810 | \$FPO | |
| | 20° x 10° | 800ft | 250ft | AT-56H-S.56HS2182010 | | |
| | 30° | 600ft | 310ft | AT-56H-S.56HS21830 | | |
| | 60° x 30° | 420ft | 420ft | AT-56H-S.56HS2186030 | | |
| | 90° | 270ft | 347ft | AT-56H-S.56HS21890 | | |
| | 150° | 185ft | 357ft | AT-56H-S.56HS218150 | | |

[†]Power supply options available; please see our power supply page.

For quantities over 10 please contact us for pricing.

PRIMARY FEATURES ~ Low Voltage - 850nm IR and Event Activated Visible Light - I/O Ports - Outdoor IP67 Rated Pan/Tilt U bracket Included

Please see our website (link below) for additional product details.

HYBRID



801 West Robinson Drive, Suite 500, North Salt Lake, UT 84054





☎ 801/519-0500 📠 801/519-0501 ✉ sales@axtontech.com ✉ orders@axtontech.com



BLAZE Series White Light

LOW VOLTAGE & PoE POWERED WHITE LIGHT

BLAZE AT-25W-S | **BLAZE AT-25WE-S** | **BLAZE AT-56W-S** | **BLAZE AT-56WE-S**

| MODEL | DESCRIPTION | ANGLE OPTIONS | RANGE | | PART NUMBER | PRICE |
|---|---|---------------|----------|-------|-----------------------|-------|
| | | | Distance | HFOV | | |
| AT-25W-S  | <ul style="list-style-type: none"> • 25 Watts • Day/Night Sensor • I/O Ports • 24-36VDC or 24VAC Input† • White Light - 3,300 lumens • Pan/Tilt U Bracket • IP67 Rated | 10° | 800ft | 140ft | AT-25W-S.25WS2110 | \$FPO |
| | | 20° x 10° | 530ft | 166ft | AT-25W-S.25WS212010 | |
| | | 30° | 400ft | 207ft | AT-25W-S.25WS2130 | |
| | | 60° x 30° | 285ft | 285ft | AT-25W-S.25WS216030 | |
| | | 90° | 175ft | 225ft | AT-25W-S.25WS2190 | |
| | | 150° | 120ft | 232ft | AT-25W-S.25WS21150 | |
| AT-25WE-S  | <ul style="list-style-type: none"> • 25 Watts • Day/Night Sensor • I/O Ports • PoE+ or PoE++ Input • White Light - 3,300 lumens • Pan/Tilt U Bracket • IP67 Rated | 10° | 800ft | 140ft | AT-25WE-S.25WES3110 | \$FPO |
| | | 20° x 10° | 530ft | 166ft | AT-25WE-S.25WES312010 | |
| | | 30° | 400ft | 207ft | AT-25WE-S.25WES3130 | |
| | | 60° x 30° | 285ft | 285ft | AT-25WE-S.25WES316030 | |
| | | 90° | 175ft | 225ft | AT-25WE-S.25WES3190 | |
| | | 150° | 120ft | 232ft | AT-25WE-S.25WES31150 | |
| AT-56W-S  | <ul style="list-style-type: none"> • 56 Watts • Day/Night Sensor • I/O Ports • 24-36VDC or 24VAC Input† • White Light - 7,200 lumens • Pan/Tilt U Bracket • IP67 Rated | 10° | 1200ft | 209ft | AT-56W-S.56WS2110 | \$FPO |
| | | 20° x 10° | 800ft | 250ft | AT-56W-S.56WS212010 | |
| | | 30° | 600ft | 310ft | AT-56W-S.56WS2130 | |
| | | 60° x 30° | 420ft | 420ft | AT-56W-S.56WS216030 | |
| | | 90° | 270ft | 347ft | AT-56W-S.56WS2190 | |
| | | 150° | 185ft | 357ft | AT-56W-S.56WS21150 | |
| AT-56WE-S  | <ul style="list-style-type: none"> • 56 Watts • Day/Night Sensor • I/O Ports • PoE++ Input • White Light - 7,200 lumens • Pan/Tilt U Bracket • IP67 Rated | 10° | 1200ft | 209ft | AT-56WE-S.56WES3110 | \$FPO |
| | | 20° x 10° | 800ft | 250ft | AT-56WE-S.56WES312010 | |
| | | 30° | 600ft | 310ft | AT-56WE-S.56WES3130 | |
| | | 60° x 30° | 420ft | 420ft | AT-56WE-S.56WES316030 | |
| | | 90° | 270ft | 347ft | AT-56WE-S.56WES3190 | |
| | | 150° | 185ft | 357ft | AT-56WE-S.56WES31150 | |

NOTE: Simplified "A" (no I/O port) or "B" (no Day/Night Sensor or I/O Ports) models are also available.

For quantities over 10 please contact us for pricing.

†Power supply options available; please see our power supply page.



PRIMARY FEATURES ~ Low Voltage and PoE Options - White Light - Day/Night Sensor - I/O Ports - Outdoor IP67 Rated
 - Pan/Tilt U bracket Included - Day/Night Sensor and/or event activated White Light

XLR Series Infrared

EXTRA LONG RANGE IR



XLR AT-115X-S | **XLR AT-170X-S**

| MODEL | DESCRIPTION | POWER OPTIONS | ANGLE OPTIONS | RANGE | | PART NUMBER | PRICE | |
|--|--|---|---------------|----------|-----------------------|-----------------------|-----------------------|-------|
| | | | | Distance | HFOV | | | |
| AT-115X-S  <ul style="list-style-type: none"> • 115 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • High or low Voltage Option • Pan/Tilt Mounting System* • IP67 Rated | Low Voltage 24-36VDC or 24VAC Input | 10° | 1690ft | 295ft | AT-115X-S.115XS2810 | \$FPO | | |
| | | 20° x 10° | 1120ft | 350ft | AT-115X-S.115XS282010 | | | |
| | | 30° | 840ft | 435ft | AT-115X-S.115XS2830 | | | |
| | | 60° x 30° | 590ft | 590ft | AT-115X-S.115XS286030 | | | |
| | | 90° | 380ft | 490ft | AT-115X-S.115XS2890 | | | |
| | | 150° | 260ft | 500ft | AT-115X-S.115XS28150 | | | |
| | | High Voltage Includes: Power Supply 110V AC to 240 VAC Input | 10° | 1690ft | 295ft | | AT-115X-S.115XS4810 | \$FPO |
| | | | 20° x 10° | 1120ft | 350ft | | AT-115X-S.115XS482010 | |
| | | | 30° | 840ft | 435ft | | AT-115X-S.115XS4830 | |
| | | | 60° x 30° | 590ft | 590ft | | AT-115X-S.115XS486030 | |
| | AT-170X-S  <ul style="list-style-type: none"> • 170 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • High or low Voltage Option • Pan/Tilt Mounting System* • IP67 Rated | Low Voltage 24-36VDC or 24VAC Input | 10° | 2075ft | 360ft | AT-170X-S.170XS2810 | \$FPO | |
| | | | 20° x 10° | 1375ft | 430ft | AT-170X-S.170XS282010 | | |
| | | | 30° | 1040ft | 520ft | AT-170X-S.170XS2830 | | |
| | | | 60° x 30° | 725ft | 725ft | AT-170X-S.170XS286030 | | |
| 90° | | | 465ft | 600ft | AT-170X-S.170XS2890 | | | |
| High Voltage Includes: Power Supply 110V AC to 240 VAC Input | | 150° | 320ft | 610ft | AT-170X-S.170XS28150 | \$FPO | | |
| | | 10° | 2075ft | 360ft | AT-170X-S.170XS4810 | | | |
| | | 20° x 10° | 1375ft | 430ft | AT-170X-S.170XS482010 | | | |
| | | 30° | 1040ft | 520ft | AT-170X-S.170XS4830 | | | |
| | | 60° x 30° | 725ft | 725ft | AT-170X-S.170XS486030 | | | |
| | | 90° | 465ft | 600ft | AT-170X-S.170XS4890 | | | |
| | | 150° | 320ft | 610ft | AT-170X-S.170XS48150 | | | |

*Requires AT-8062-(C, P or W) Mounting Bracket for Installation.

For quantities over 10 please contact us for pricing.

PRIMARY FEATURES ~ 850nm Infrared - Day/Night Sensor - I/O Ports - Outdoor IP67 Rated - Pan/Tilt Mounting System Included*

Please see our website (link below) for additional product details.

XLR



801 West Robinson Drive, Suite 500, North Salt Lake, UT 84054

☎ 801/519-0500 📠 801/519-0501 ✉ sales@axtontech.com ✉ orders@axtontech.com



PANORAMIC 180° Infrared






EXTRA WIDE ANGLE IR

AT-33S-180P

AT-75S-180P

AT-170S-180P

| MODEL | DESCRIPTION | RANGE | | POWER OPTIONS | PART NUMBER | PRICE |
|--|---|--------------|-------------|--|-------------------------|--------------|
| | | Distance | Coverage | | | |
| AT-33S-180P  | <ul style="list-style-type: none"> • 33 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 190ft | 180° | Low Voltage 24-36VDC or 24VAC Input | AT-33S-180P.33SP28180 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-33S-180P.33SP48180 | \$FPO |
| AT-75S-180P  | <ul style="list-style-type: none"> • 75 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 280ft | 180° | Low Voltage 24-36VDC or 24VAC Input | AT-75S-180P.75SP28180 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-75S-180P.75SP48180 | \$FPO |
| AT-170S-180P  | <ul style="list-style-type: none"> • 170 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 420ft | 180° | Low Voltage 24-36VDC or 24VAC Input | AT-170S-180P.170SP28180 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-170S-180P.170SP48180 | \$FPO |

*Requires AT-8062-(C, P or W) Mounting Bracket for Installation.

For quantities over 10 please contact us for pricing.

PRIMARY FEATURES ~ 850nm Infrared - Day/Night Sensor - I/O Ports - Outdoor IP67 Rated - Pan/Tilt Mounting System Included*

Please see our website (link below) for additional product details.

PANORAMIC



801 West Robinson Drive, Suite 500, North Salt Lake, UT 84054





☎ 801/519-0500 📠 801/519-0501 ✉ sales@axtontech.com ✉ orders@axtontech.com



PANORAMIC 270° Infrared

EXTRA WIDE ANGLE IR

AT-22S-270P | **AT-50S-270P** | **AT-115S-270P** | **AT-170S-270P**

| MODEL | DESCRIPTION | RANGE | | POWER OPTIONS | PART NUMBER | PRICE |
|--|--|----------|----------|--|-------------------------|-------|
| | | Distance | Coverage | | | |
| AT-22S-270P  | <ul style="list-style-type: none"> • 22 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 85ft | 270° | Low Voltage 24-36VDC or 24VAC Input | AT-22S-270P.22SP28270 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-22S-270P.22SP48270 | \$FPO |
| AT-50S-270P  | <ul style="list-style-type: none"> • 50 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 123ft | 270° | Low Voltage 24-36VDC or 24VAC Input | AT-50S-270P.50SP28270 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-50S-270P.50SP48270 | \$FPO |
| AT-115S-270P  | <ul style="list-style-type: none"> • 115 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 185ft | 270° | Low Voltage 24-36VDC or 24VAC Input | AT-115S-270P.115SP28270 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-115S-270P.115SP48270 | \$FPO |
| AT-170S-270P  | <ul style="list-style-type: none"> • 170 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 270ft | 270° | Low Voltage 24-36VDC or 24VAC Input | AT-170S-270P.170SP28270 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-170S-270P.170SP48270 | \$FPO |

*Requires AT-8062-(C, P or W) Mounting Bracket for Installation.

For quantities over 10 please contact us for pricing.

PRIMARY FEATURES ~ 850nm Infrared - Day/Night Sensor - I/O Ports - Outdoor IP67 Rated - Pan/Tilt Mounting System Included*

Please see our website (link below) for additional product details.

PANORAMIC

PANORAMIC 360° Infrared






EXTRA WIDE ANGLE IR

AT-33S-360P

AT-75S-360P

AT-170S-360P

| MODEL | DESCRIPTION | RANGE | | POWER OPTIONS | PART NUMBER | PRICE |
|--|--|----------|----------|--|-------------------------|-------|
| | | Distance | Coverage | | | LIST |
| AT-33S-360P  | <ul style="list-style-type: none"> • 33 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 85ft | 360° | Low Voltage 24-36VDC or 24VAC Input | AT-33S-360P.33SP28360 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-33S-360P.33SP48360 | \$FPO |
| AT-75S-360P  | <ul style="list-style-type: none"> • 75 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 123ft | 360° | Low Voltage 24-36VDC or 24VAC Input | AT-75S-360P.75SP28360 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-75S-360P.75SP48360 | \$FPO |
| AT-170S-360P  | <ul style="list-style-type: none"> • 170 Watts • Day/Night Sensor • I/O Ports • 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 185ft | 360° | Low Voltage 24-36VDC or 24VAC Input | AT-170S-360P.170SP28360 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-170S-360P.170SP48360 | \$FPO |

*Requires AT-8062-(C, P or W) Mounting Bracket for Installation.

For quantities over 10 please contact us for pricing.

PRIMARY FEATURES ~ 850nm Infrared - Day/Night Sensor - I/O Ports - Outdoor IP67 Rated - Pan/Tilt Mounting System Included*

Please see our website (link below) for additional product details.

PANORAMIC



801 West Robinson Drive, Suite 500, North Salt Lake, UT 84054

☎ 801/519-0500 📠 801/519-0501 ✉ sales@axtontech.com 📧 orders@axtontech.com






HYBRID PANORAMIC 180° IR & White



EXTRA WIDE ANGLE IR & EVENT ACTIVATED WHITE LIGHT

[AT-33H-S-180P](#) | [AT-75H-S-180P](#) | [AT-170H-S-180P](#)

| MODEL | DESCRIPTION | RANGE | | POWER OPTIONS | PART NUMBER | PRICE |
|--|--------------|-------------|--|--------------------------|--------------|-------|
| | | Distance | Coverage | | | |
|  AT-33H-S-180P • 33 Watts • I/O Ports • Visible/ 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 190ft | 180° | Low Voltage 24-36VDC or 24VAC Input | AT-33H-180P.33HP218180 | \$FPO | |
| | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-33H-180P.33HP418180 | \$FPO | |
|  AT-75H-S-180P • 75 Watts • I/O Ports • Visible/ 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 280ft | 180° | Low Voltage 24-36VDC or 24VAC Input | AT-75H-180P.75HP218180 | \$FPO | |
| | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-75H-180P.75HP418180 | \$FPO | |
|  AT-170H-S-180P • 170 Watts • I/O Ports • Visible/ 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 420ft | 180° | Low Voltage 24-36VDC or 24VAC Input | AT-170H-180P.170HP218180 | \$FPO | |
| | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-170H-180P.170HP418180 | \$FPO | |

*Requires AT-8062-(C, P or W) Mounting Bracket for Installation.

For quantities over 10 please contact us for pricing.

PRIMARY FEATURES ~ 850nm IR and Event Activated Visible Light - I/O Ports - Outdoor IP67 Rated - Pan/Tilt Mounting System Included*
 Please see our website (link below) for additional product details.

HYBRID PANORAMIC



801 West Robinson Drive, Suite 500, North Salt Lake, UT 84054

☎ 801/519-0500 📠 801/519-0501 ✉ sales@axtontech.com 📧 orders@axtontech.com







HYBRID PANORAMIC 270° IR & White



EXTRA WIDE ANGLE IR & EVENT ACTIVATED WHITE LIGHT

AT-22H-S-270P | AT-50H-S-270P | AT-115H-S-270P | AT-170H-S-270P

| MODEL | DESCRIPTION | RANGE | | POWER OPTIONS | PART NUMBER | PRICE |
|--|--------------|-------------|--|--------------------------|--------------|-------|
| | | Distance | Coverage | | | |
| AT-22H-S-270P  <ul style="list-style-type: none"> • 22 Watts • I/O Ports • Visible/ 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 85ft | 270° | Low Voltage 24-36VDC or 24VAC Input | AT-22H-270P.22HP218270 | \$FPO | |
| | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-22H-270P.22HP418270 | \$FPO | |
| AT-50H-S-270P  <ul style="list-style-type: none"> • 50 Watts • I/O Ports • Visible/ 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 123ft | 270° | Low Voltage 24-36VDC or 24VAC Input | AT-50H-270P.50HP218270 | \$FPO | |
| | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-50H-270P.50HP418270 | \$FPO | |
| AT-115H-S-270P  <ul style="list-style-type: none"> • 115 Watts • I/O Ports • Visible/ 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 185ft | 270° | Low Voltage 24-36VDC or 24VAC Input | AT-115H-270P.115HP218270 | \$FPO | |
| | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-115H-270P.115HP418270 | \$FPO | |
| AT-170H-S-270P  <ul style="list-style-type: none"> • 170 Watts • I/O Ports • Visible/ 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 270ft | 270° | Low Voltage 24-36VDC or 24VAC Input | AT-170H-270P.170HP218270 | \$FPO | |
| | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-170H-270P.170HP418270 | \$FPO | |

*Requires AT-8062-(C, P or W) Mounting Bracket for Installation.

For quantities over 10 please contact us for pricing.

PRIMARY FEATURES ~ 850nm IR and Event Activated Visible Light - I/O Ports - Outdoor IP67 Rated - Pan/Tilt Mounting System Included*

Please see our website (link below) for additional product details.

HYBRID PANORAMIC



801 West Robinson Drive, Suite 500, North Salt Lake, UT 84054

☎ 801/519-0500 📠 801/519-0501 ✉ sales@axtontech.com 📧 orders@axtontech.com






HYBRID PANORAMIC 360° IR & White



EXTRA WIDE ANGLE IR & EVENT ACTIVATED WHITE LIGHT

[AT-33H-S-360P](#) | [AT-75H-S-360P](#) | [AT-170H-S-360P](#)

| MODEL | DESCRIPTION | RANGE | | POWER OPTIONS | PART NUMBER | PRICE |
|---|---|--------------|-------------|--|--------------------------|--------------|
| | | Distance | Coverage | | | |
|  AT-33H-S-360P | <ul style="list-style-type: none"> • 33 Watts • I/O Ports • Visible/ 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 80ft | 360° | Low Voltage 24-36VDC or 24VAC Input | AT-33H-360P.33HP218360 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-33H-360P.33HP418360 | \$FPO |
|  AT-75H-S-360P | <ul style="list-style-type: none"> • 75 Watts • I/O Ports • Visible/ 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 120ft | 360° | Low Voltage 24-36VDC or 24VAC Input | AT-75H-360P.75HP218360 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-75H-360P.75HP418360 | \$FPO |
|  AT-170H-S-360P | <ul style="list-style-type: none"> • 170 Watts • I/O Ports • Visible/ 850nm IR • Includes Junction Box • Pan/Tilt Mounting System* • IP67 Rated | 185ft | 360° | Low Voltage 24-36VDC or 24VAC Input | AT-170H-360P.170HP218360 | \$FPO |
| | | | | High Voltage Includes Power Supply 110V AC to 240 VAC Input | AT-170H-360P.170HP418360 | \$FPO |

*Requires AT-8062-(C, P or W) Mounting Bracket for Installation.

For quantities over 10 please contact us for pricing.

PRIMARY FEATURES ~ 850nm IR and Event Activated Visible Light - I/O Ports - Outdoor IP67 Rated - Pan/Tilt Mounting System Included*

Please see our website (link below) for additional product details.

HYBRID PANORAMIC




801 West Robinson Drive, Suite 500, North Salt Lake, UT 84054

☎ 801/519-0500 📠 801/519-0501 ✉ sales@axtontech.com 📧 orders@axtontech.com



POWER SUPPLIES







| AC/DC POWER SUPPLIES UNIVERSAL INPUT | DESCRIPTION | | PART NUMBER | PRICE |
|--|---|---------------|-------------|-------|
| 25 Watts Output: 24 VDC Input: 88-264 VAC, 47-63 Hz | <ul style="list-style-type: none"> • Rugged die cast aluminum enclosure • overload/overvoltage protection • environmental rating: IP 66/ NEMA 4X | single output | AT8021 | \$FPO |
| | | single output | AT8022 | |
| | | dual output | AT8022-2 | |
| 50 Watts Output: 24 VDC Input: 88-264 VAC, 47-63 Hz | <ul style="list-style-type: none"> • Rugged die cast aluminum enclosure • overload/overvoltage protection • environmental rating: IP 66/ NEMA 4X | single output | AT8022-3 | \$FPO |
| | | dual output | AT8022-2 | |
| | | triple output | AT8022-3 | |
| 75 Watts Output: 24 VDC Input: 88-264 VAC, 47-63 Hz | <ul style="list-style-type: none"> • Rugged die cast aluminum enclosure • overload/overvoltage protection • environmental rating: IP 66/ NEMA 4X | single output | AT8023 | \$FPO |
| | | dual output | AT8023-2 | |
| | | triple output | AT8023-3 | |
| 100 Watts Output: 24 VDC Input: 88-264 VAC, 47-63 Hz | <ul style="list-style-type: none"> • Rugged die cast aluminum enclosure • overload/overvoltage protection • environmental rating: IP 66/ NEMA 4X | single output | AT8024 | \$FPO |
| | | dual output | AT8024-2 | |
| | | triple output | AT8024-3 | |
| 150 Watts Output: 24 VDC Input: 88-264 VAC, 47-63 Hz | <ul style="list-style-type: none"> • Rugged die cast aluminum enclosure • overload/overvoltage protection • environmental rating: IP 66/ NEMA 4X | single output | AT8026 | \$FPO |
| | | dual output | AT8026-2 | |
| | | triple output | AT8026-3 | |
| 230 Watts Output: 24 VDC Input: 88-264 VAC, 47-63 Hz | <ul style="list-style-type: none"> • Rugged die cast aluminum enclosure • overload/overvoltage protection • environmental rating: IP 66/ NEMA 4X | single output | AT8029 | \$FPO |
| | | dual output | AT8029-2 | |
| | | triple output | AT8029-3 | |
|  12 Watts | <ul style="list-style-type: none"> • Output: 12 VDC • Standard Power Adapter • Indoor use only • USA: two prong plug | single output | AT8010C | \$FPO |

Please see our website (link below) for additional product details.

For quantities over 10 please contact us for pricing.

POWER SUPPLIES

BRACKETS & MOUNTING ADAPTERS

| | DESCRIPTION | PART NUMBER | PRICE |
|--|---|-------------|-------|
| L-BRACKET  FREE to swap with U bracket | L-Bracket, Large, Fits Med. and Lrg. Illuminator (15W & above) | AT-8052 | |
| | L-bracket, Small, Fits Small Illuminator (11W and under) | AT-8054 | |
| Mounting Adapters  Wall/Corner Pole | Corner Mounting Adapter for Multi Panel Units* or Single** with panning adapter (below). | AT-8062-C | |
| | Pole Mounting Adapter for Multi Panel Units* or Single** with panning adapter (below). | AT-8062-P | |
| | Wall Mounting Adapter for Multi Panel Units* or Single** with panning adapter (below) | AT-8062-W | |
| Panning Adapter Single-Panel Units  | Panning Adapter fits single panel units. Mount directly to surface or use with corner, pole or wall mounting adapter above. | AT-8062 | |
| Panning Mounts Single-Panel Units  Wall/Corner Pole | Corner Panning Mount use with any single panel unit. | AT-8069-C | |
| | Pole Panning Mount use with any single panel unit. | AT-8069-P | |
| | Wall Panning Mount use with any single panel unit. | AT-8069-W | |
| Mobotix M15 Bracket  FREE to swap with U bracket | Fits Sm. Illuminator; mount directly to Mobotix M15 Camera | AT-M15S | |
| | Fits Med. Illuminator; mount directly to Mobotix M15 Camera | AT-M15M | |
| | Fits Lrg. Illuminator; mount directly to Mobotix M15 Camera | AT-M15L | |
| Mobotix M25 Bracket  FREE to swap with U bracket | Fits Sm. Illuminator; mount directly to Mobotix M25 Camera | AT-M25S | |
| | Fits Med. Illuminator; mount directly to Mobotix M25 Camera | AT-M25M | |
| | Fits Lrg. Illuminator; mount directly to Mobotix M25 Camera | AT-M25L | |

For quantities over 10 please contact us for pricing.

*Use Mounting Adapters with Illuminators that have Pan/Tilt Mounting Systems e.g. Panoramic & XLR Series.

**To use a Mounting Adapter with a single illuminator you will also need a panning adapter AT-8052.

BRACKETS